

# 2D Numerical Study Of The Velocity Profile In An Laminar Flow With Solid Particles On A Flat Plate

O. Ayala<sup>1</sup>

<sup>1</sup>Old Dominion University

## Abstract

This article presents a two-dimensional numerical study of the velocity profile of an incompressible laminar flow with particles on a flat plate. The model was developed using COMSOL MULTYPHISICS 6.0 software. Various cases present varying parameters such as volumetric fraction of particles ( $\phi$ ), relative particle size ( $R_{sp}$ ) and Stokes number ( $St_k$ ), entry velocity of particles ( $V_p$ ), and particle entrance zone ( $H$ ). This study focused on observing how these parameters affect the fluid flow profile velocity. The velocity profile of particle-laden flows was compared to the Blasius velocity profile (particle-free flow). The results show three zones, the first zone near the plate is an acceleration zone (when  $V_p=V_f$ ) or deceleration zone (when  $V_p<V_f$ ); a third zone away from the plate where no acceleration or deacceleration is produced; and a second zone that works as a transition to go from the affected zone to the non-affected zone. These particles interfere with the development of velocity profiles and increase proportionally with the volumetric fraction of particles ( $\phi$ ), while it occurs inversely proportional to the relative particle size ( $R_{sp}$ ). Increasing the Stokes number also generates variation in the flow. Additionally, it was found that the volume fraction of particles ( $\phi$ ) and the relative particle size ( $R_{sp}$ ) have a linear proportionality with the relative variation of the fluid velocity. For cases with low particle presence, the effects of the particle can be disregarded and considered the flow as particle-free flow, as well as for low Stokes numbers.

## Reference

- [1] Osipov, A.N. (1980). Structure of the laminar boundary layer of a dispersed medium on a flat plate. *Proceedings from Fluid Dynamics* 15(4):512-517 DOI: 10.1007/BF01089608.
- [2] Asmolov, E.S. and Manuilovich, S.V. (1998). Stability of a dusty-gas laminar boundary layer on a flat plate. *Proceedings from Fluid Dynamics*. DOI: 10.1017/S0022112098001256.
- [3] Cengel, Y. and Cimbala, J. (2006). *Mecánica de Fluidos Fundamentos y Aplicaciones*. Primera Edición. Editorial McGraw-Hill. México.
- [4] Villalba, O. Ayala, O. F. and Ayala, O. M. (2022). Numerical study of erosion wear on the disc of a butterfly valve with laminar particle-laden flows in a horizontal pipeline. *Proceedings of the ASME 2022. International Mechanical Engineering Congress and Exposition*. IMECE2022-94738. Columbus, Ohio, UT, USA.
- [5] González, E., Navarrete, L., Ayala, O., Ayala, F. and Ayala, M. (2023). Numerical study of the friction coefficient of an incompressible laminar flow with solid particles over a flat plate. *Proceedings of the ASME 2023. International Mechanical Engineering Congress and Exposition*. IMECE2023-111962. New Orleans, LA, USA.
- [6] Marín, J., Amaya, C., Ayala, O., Ayala, F. and Ayala, M. (2023). Numerical study of the velocity profiles in an incompressible laminar flow with particles between two parallel plates. *Proceedings of the ASME 2023. International Mechanical Engineering Congress and Exposition*. IMECE2023-113888. New Orleans, LA, USA.

